









30H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Key Features:

• Frequency range: DC ÷ 1000 Hz

Dynamic Range: 70 dB

Directivity: Isotropic

Sensitivity > 200 μT

• High pass filter (cut-off @ 1.5Hz).

Compatibility:

NHT310 and NHT3D meters

Typical Application:

- · Locations where there are patients with pacemakers
- MRI Magnetic Resonance Imaging
- Galvanic treatments
- Railway Power Supply Plants
- Metalworking processes

















30H PROBE

Magnetic Field Probe: B Field, DC ÷ 1000 Hz

Description:

The 30H probe is based on a set of three mutually orthogonal Hall sensors. The three voltages, which correspond to the spatial components of the field, are available individually at the probe output. The NHT 310 or NHT 3D meter calculates the resulting isotropic field strength.

The probe detects magnetic fields from 0 to 1000 Hz. It is suitable for use in applications such as Magnetic Resonances Imaging (MRI), materials working plants (galvanic and mills) and power supply plants for railway stations.

The high sensitivity of this probe makes it ideal for exposure measurements in sensitive environments, such as places where people using peacemakers are present.

The presence of a first-order high-pass filter (20 dB / decade) with a 1.5Hz cutting frequency allows to discriminate the static component from the others at higher frequencies. In fact, the filter, when inserted, completely suppresses the continuous component and the probe band becomes 1.5 Hz \div 1000 Hz.

TECHNICAL SPECIFICATIONS		
Frequency range	0 ÷ 1000 Hz	
Type of frequency response	Flat	
Measurement range	200 μT ÷ 600 mT	
Dynamic range	70 dB	
Sensor type	Hall sensors	
Directivity	Isotropic	
Frequency response	± 0.5 dB (0 Hz ÷1 kHz)	
Linearity	± 0.7 dB (5 ÷ 550 mT)	
Isotropic response	± 0.5 dB (@ 10 mT)	

GENERAL CHARACTERISTICS		
Recommended calibration interval	24 months	
Operating temperature	0℃ ÷ 50℃	
Size	300 x 16 Ø (mm)	
Weight	63 g	
Country of origin	Italy	



