


Характеристики:

- Широкий диапазон
- Высокая чувствительность
- Низкий КСВН
- Без смещений
- Возможны изменения по требованию заказчика



Parameters	Min.	Typ.	Max.	Units
Frequency Range	6		18	GHz
VSWR		1.4	1.5	: 1
Tss	-25			dBm
Sensitivity		0.5		mv/uW
Input Power			23	dBm
Output Polarity	Positive			
Weight	0.48 Max.			ounces
Input / Output Connectors	SMA-Male / SMA-Female			
Material	Aluminum			
Finish	Gold Plated			


Широкополосный детектор мощности 6 - 18 ГГц

Environmental Specifications

Operational Temperature(°C)	-40°C~+85°C
Storage Temperature (°C)	-50°C~+105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions


Outline Drawing:

All Dimensions in mm (inches) Housing Tolerance ±0.1(0.004)




Широкополосный детектор мощности 6 - 18 ГГц


VSWR @+25°C




VSWR @-40°C




VSWR @+85°C



Output DC Voltage vs. Input Power



Rise Time



Fall Time

