

Communications & Power Industries Pulsed Amplifier



Compact

Eight rack-units tall (14 in/356 mm).

Versatile

Wide band, automatic fault recycle, user-friendly microprocessor-controlled logic with integrated computer interface, digital metering, and quiet operation suitable for laboratory environments. An integral solid state preamplifier and IEEE interface are included as standard features.

Global Applications

230 VAC operation. Designed to meet International Safety Standard EN61010 and Electromagnetic Compatibility 2004/108/EC.

Easy to Maintain

Modular design and built-in fault diagnostic capability.

Worldwide Support

Backed by CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.

With a history of producing high quality products, we can help you with your pulsed

FEATURES:

- Rack mountable
- Waveguide output
- GPIB remote

BENEFITS:

- Compact high pulsed power
- Single phase AC power
- Local or remote control
- Wide RF bandwidth

APPLICATIONS:

- Test and measurement systems

CPI Ku-Band 3.25 kW Compact Pulsed Amplifier: VZU3530J1

SPECIFICATIONS

Frequency	12.0 to 18.0 GHz
Output power (min.) flange	3250 W
Gain	65 dB min. at rated power (with no RF options); >67 dB min. at small signal (with no RF options)
Gain adjustment range	20 dB min.
Input VSWR	2.5:1 typical
Output VSWR	2.5:1 typical
Load VSWR	1.5:1 max. for full spec. compliance; May oscillate with unshielded open due to coupling to input. Should not be tested with connector off
Pulsewidth	0.1 μ s to 100 μ s
PRF	50 kHz max.
Duty cycle	6% max.
Delay	400 ns typical:
Droop	0.5 dB over 50 μ s
NPO	-10 dBm/MHz Beam on: -110 dBm/MHz Beam off
Primary power	220-240 VAC, single phase 47-63 Hz
Power consumption	2.2 kVA typical
Filament voltage	Reduction of 10% in standby for extended TWT life
Inrush current	200% max.
Ambient temperature	-10° to +40°C operating -40° to +70°C non-operating
Relative humidity	95% non-condensing
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft., operating; 40,000 ft., non-operating
Shock and vibration	As normally encountered in a protected laboratory environment
Cooling	Forced air with integral blower Rear air intake and exhaust; 0.10" water max. external pressure loss allowable
RF Input connection	Type N female
RF Output connection	WRD-350 waveguide flange
Dimensions	19 x 14 x 26in. (483 x 356 x 661 mm) Excluding connectors, fans. Handles and exhaust duct
Weight	150 lbs. (68 kg) max.
Heat dissipation	\approx 1600 W
Safety	ENG61010
Acoustic noise	65 dBA @ 3 ft. from amplifier