


Характеристики:

- Широкий диапазон
- Высокая чувствительность
- Низкий КСВН



Parameters	Min.	Typ.	Max.	Units
Frequency Range	0.5-8			GHz
VSWR			1.2	: 1
Tss		-30		dBm
Sensitivity		0.5		Mv / uw
Input Power			23	dBm
Output Polarity	Positive (+)			
Weight	0.35 Max.			Ounces
Input / Output Connectors	SMA-Male / SMA-Female			
Material	Aluminum			
Finish	Gold Plated			


Широкополосный детектор мощности 0,5 - 8 ГГц

Environmental Specifications

Operational Temperature(°C)	-45°C to +85°C
Storage Temperature (°C)	-50°C to +105°C
Altitude	30,000 ft. (Epoxy Sealed Controlled environment)
	60,000 ft. 1.0psi min (Hermetically Sealed Un-controlled environment) (Optional)
Vibration	25g RMS (15 degrees 2KHz) endurance, 1 hour per axis
Humidity	100% RH at 35°C, 95%RH at 40°C
Shock	20G for 11msec half sine wave,3 axis both directions


Outline Drawing:

All Dimensions in mm (inches) Tolerance $\pm 0.15(0.006)$




Широкополосный детектор мощности 0,5 - 8 ГГц


VSWR @+25°C




VSWR @-45°C




VSWR @+85°C



Output DC Voltage VS. Input Power



Rise time



Fall time

