

# SI-300 Camera Controller

## Product Overview

**Multi-Camera Control** The TDK SI-300CC Camera Controller is capable of controlling up to four independent camera units. It allows precision manipulation of camera features such as pan, tilt, zoom, and focus with the use of two joysticks. In addition, the SI-300CC comes fully equipped with a graphical LCD, four function keys, four special keys, and twelve numerical keys for user-friendly control.

**Flexibility** The SI-300CC can be operated manually or through an IEEE 488 interface. The camera controller can be rack mounted or used as a stand-alone unit.

**Audio Monitoring** The SI-300CC can also be utilized for audio monitoring when used with a TDK VC-04 video camera optioned with an internal microphone.

**Signal Conversion** The controller contains up to four fiber optic video receivers, which convert the fiber optic video signal to a standard 75 ohm analog video signal for use in standard video equipment.

## Applications

- EUT monitoring
- Shielded chamber monitoring
- Multiple camera manipulation



**The TDK SI-300CC Camera Controller can control up to four remote video cameras. Manipulation of camera features such as pan, tilt, zoom, and focus can be accomplished via user-friendly joysticks or built-in function keys.**

## System Features

- Capable of controlling up to four remote video camera units using fiber optic interfaces
- Camera control features pan, tilt, zoom, focus, iris control
- Graphical 240 x 64 LCD display
- Keyboard control with four function keys
- Easy to operate ergonomic controls
- GPIB control for front panel functions
- Built-in fiber optic video receiver(s)
- Supports NTSC or PAL
- Optional built-in audio receiver(s)

# 4TECT

ООО «4TECT»

Телефон: +7(499)685-4444

[info@4test.ru](mailto:info@4test.ru)

[www.4test.ru](http://www.4test.ru)

# SI-300 Camera Controller

## Mechanical Specifications

Overall Dimensions: 3.5" H x 17.7" W x  
10.5" D (8.8 cm x 44.8  
cm x 26.6 cm)

## Electrical Specifications

Power Requirements 100-240 VAC, 50-60  
Hz, 45 W

Communication Media Fiber optic cable  
(ST connectors);  
Bi-direction asynchro-  
nous serial

Display Resolution 240 x 64 backlit LCD

Channel Capacity 4 fiber channels

## Environmental Specifications

### Ambient Temperature Limits

Operating: 0° to +40° C

Storage: -10° to +50° C

Humidity: Up to 90% non-  
condensing

## Ordering Information

Product: Camera Controller

Model Number: SI-300CC

Warranty: 1 year

**To place an order or to learn more about the  
TDK products that best meet your needs, con-  
tact your TDK sales representative:**



ООО «4ТЕСТ»  
Телефон: +7(499)685-4444  
[info@4test.ru](mailto:info@4test.ru)  
[www.4test.ru](http://www.4test.ru)

TOTAL RF EXPERTISE™

