

For EMC/EMI and other instrumentation applications.

Provides a minimum of up to 45 watts of power at the flange in a compact package, across the 18.0 to 26.5 frequency range.

Easy to Use and Versatile

Extensive diagnostic capability. Automatic output power control. Time stamped event log. Automatic filament shutdown. Manual override control. Dual communications interfaces. Continuous RF attenuator adjustment in 0.1 dB steps.

Ruggedly Built

Meets MIL-STD-810E.

Meets Global Requirements

Meets International Safety Standard EN61010 and Electromagnetic Compatibility 2014/30/EU.

Worldwide Support

Backed by over 40 years of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.



CPI 40/50 W CW Ka-band TWTA, Model TE01KO-C

OPTIONS:

- RF input attenuator
- Gain Variation Equalizer
- Integral linearizer
- Mounting configurations
- Low gain (remove SSIPA)
- Ethernet interface
- Others available upon request

Quality Management
System - ISO 9001:2015



Specification	CPI Model TE01KO-C, 40/50 W CW K-band TWTAs
Frequency	18.0 to 26.5 GHz
Output Power (min.), TWT Output Power (min.), Flange	40 W CW or 50 W CW 34 W CW or 44 W CW
Bandwidth	8.5 GHz
Gain	46 dB typ. at rated power output
RF Level Adjust Range	0 to 20 dB
Gain Stability	±0.25 dB/24 hr max. (after 30 minute warmup and at constant drive and temperature)
Gain Variation	±6.0 dB max. (+/-3.0 dB max. with gain variation equalizer option)
VSWR Input Output Load	2.0:1 max. 2.5:1 typ. 2.0:1 max.
Harmonic Content	-6 dB max.
Noise and Spurious	-50 dBc typ. excluding harmonics
Prime Power	100 to 264 VAC single phase, 2 wire, 47 to 63 Hz
Power Consumption	600 VA nom.
Inrush Current	200%
Operating Temperature	-40°C to +50°C (derate by 1.9°C per 1,000 ft. above sea level)
Non-Operating Temperature	-50°C to +70°C
Relative Humidity	100% condensing
Operating Altitude	10,000 ft above sea level (3,048 m)
Non-Operating Altitude	50,000 ft above sea level (15,240 m)
Vibration	MIL-STD-810E, Method 514.4, Procedure 1, Category 1
Shock	10 g, 11 ms half sine
Acoustic Noise	<68 dBA max. at 1 meter
Air Flow	150 cfm
Cooling	Forced air, 2.0" clearance required
Input RF Connector	Type K Female
Output RF Connector	WR42G
Dimensions	9.6" H x 11.8" W x 20.6" L (244 x 300 x 522 mm)
Weight	49 lbs (22.2 kg) nom.